







1U,3U,W6U Standard type General Specifications

Item	1U		3U		W6U								
	Type A	Type B	Type A	Type B	Type A	Type B							
Appearance													
	Main.FL	Boutless Structure 1UA	Boutless Structure 1UB	Boutless Structure 3UA	Boutless Structure 3UB	Boutless Structure W6UA	Boutless Structure W6UB						
±Z panel	Panel separation type	Switch integrated type	Panel separation type	Switch integrated type	Panel separation type	Panel separation type							
±X,Y panel	Panel separation type (t2X82X97.5)		Panel separation type (t2X100X326.5)										
Attributes (DS:Deployment Switch, SP:Spring Plunger)	<ul style="list-style-type: none"> <li>•DS and SP can be attached to the rail part of Main.FL.</li> <li>•Z-direction opening shape approx. 92cm<sup>2</sup> (Excluding rail section)</li> <li>•Y,X direction opening shape approx. 70cm<sup>2</sup> (Excluding corners)</li> </ul>		<ul style="list-style-type: none"> <li>• ±Z to panel DS and SP can be installed.</li> <li>•Z-direction opening approx. 94cm<sup>2</sup> (Excluding rail section)</li> <li>•Y,X direction opening shape approx. 69cm<sup>2</sup> (Excluding corners)</li> </ul>		<ul style="list-style-type: none"> <li>•DS and SP can be attached to the rail part of Main.FL.</li> <li>•Z-direction opening approx. 92cm<sup>2</sup> (Excluding rail section)</li> <li>•Y,X direction opening shape approx. 68、98cm<sup>2</sup> (Excluding corners)</li> </ul>		<ul style="list-style-type: none"> <li>• ±Z to panel DS and SP can be installed.</li> <li>•Z-direction opening approx. 92cm<sup>2</sup> (Excluding corners)</li> <li>•Y,X direction opening shape approx. 70、87cm<sup>2</sup> (Excluding corners)</li> </ul>						
	<ul style="list-style-type: none"> <li>• ±Z,Y,X panel integrated (integrated assembly) type on Main.FL</li> <li>•Z-direction opening approx. 213cm<sup>2</sup> (Excluding rail section)</li> <li>•Y direction opening shape approx. 173、247cm<sup>2</sup> (Excluding corners)</li> </ul>		<ul style="list-style-type: none"> <li>• ±Z,Y,X panel assembly type</li> <li>•Z-direction opening approx. 213cm<sup>2</sup> (Excluding rail section)</li> <li>•Y direction opening shape approx. 173、248cm<sup>2</sup> (Excluding corners)</li> </ul>										
Materials used							Aluminum alloy (JIS 2000 series, 5000 series, 6000 series, 7000 series)						
Size (mm)	Length	100		100		100							
	Width	100		100		226.3							
	Height	113.5		340.5		340.5 or 366							
Weight (g) Y,X Excluding panels		143	110	344	299	998	559						
Applicable documents							JX-ESPEC-101132-E						